

Material Safety Data Sheet



XaarJet AB
Box 516,
SE-175 26 Järfälla
Sweden
Tel. +46 8 580 887 00
www.xaar.co.uk

1. Identification of the substance

Product name: Xaar Oil-based Development Ink, IK820

2. Composition / information on ingredients

Chemical Nature: A preparation containing pigment dyestuff and aliphatic hydrocarbon.

Ingredient name	Einecs No.	CAS No.	Contents	Symbol	Risk (R No.)
Distillates (petroleum), Hydrotreated light; Kerosine - unspecified	265-149-8	64742-47-8	10-30%	Xn	65
Petroleum Distillate	265-148-2	64742-46-7	30-60%	Xn	65,66

Risk phrases, explanations:

R65 = Harmful: May cause lung damage if swallowed, R66 = Repeated exposure may cause skin dryness or cracking.

3. Hazard identification

Risk advice to man and the environment

This health hazard assessment is based on a consideration of the composition of this product.

Not regarded as a health or environmental hazard under current legislation

4. First aid measures

- Inhalation:** Do not induce vomiting! Never make an unconscious person vomit or drink fluids! Remove victim immediately from source of exposure.
- Skin contact:** Remove contaminated clothing. Wash skin with water. If symptoms develop, obtain medical attention. Contaminated clothing should be laundered before re-issue.
- Eye contact:** Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes. Obtain medical attention if irritation persists.
- Ingestion:** Wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Do not induce vomiting. Never make an unconscious person vomit or drink fluids! If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Obtain medical attention.

Notes to physician

- Treatment:** Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours as delayed pulmonary oedema may develop.
-

5. Fire fighting measures

- Suitable extinguishing media:** Foam, CO₂ or dry powder.
Water spray should only be used to cool containers.
- Specific hazards during fire fighting:** Not classed as flammable.
Containers close to fire should be removed immediately or cooled with water. Keep run-off water out of sewers and water sources.

May ignite if strongly heated. No unusual fire or explosion hazards noted.
- Special protective equipment for fire-fighters:** A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

6. Accidental release measures

Personal precautions:	Ensure suitable personal protection during removal of spillages. Avoid contact with skin and eyes Exclude sources of ignition and ventilate area.
Environmental precautions:	Do not allow to enter drains, sewers or watercourses.
Methods for cleaning up:	Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Wash the spillage area clean. Washings must be prevented from entering surface water drains. Wear necessary protective equipment.

7. Handling and storage

Handling

Advice on protection against fire and Explosion:

Take precautionary measures against static discharges. Keep away from heat and sources of ignition.

Advice on safe handling:

Use only in well ventilated areas.
Avoid contact with skin and eyes.
Avoid inhalation of high concentrations of vapour/mist.

Storage

Requirements for storage areas and containers:

Keep container tightly closed.
Protect from light, including direct sun.
Ground container and transfer equipment to avoid static discharges.

Materials not to be stored together:

Keep away from strong oxidising agents

8. Exposure controls / personal protection

Ingredient name	CAS No	STD	LT EXP (8Hrs)	St EXP (15 min)
Petroleum distillate	64742-46-47		200 ppm	

Ingredient comments: OES= Occupational exposure standard

Engineering measures

Where suitable engineering controls are not fitted or are inadequate, wear suitable protective equipment.

Personal protection equipment

Respiratory protection:	Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely.
Hand protection:	Wear suitable gloves.
Eye protection:	Wear eye/face protection.
Skin and body protection:	Wear suitable protective clothing.

9. Physical and chemical properties

Appearance:	Liquid
Colour:	Various
Odour:	Characteristic, oil. Hydrocarbon. Fishy
Boiling point (°C):	200-300
Flash point (°C) (CC):	120
Autoignition Temperature (°C):	200
Evaporation rate:	<0.05 (BuAc=1)
Vapour pressure (mmHg, 25°C):	<1
Vapour density (air = 1)	>1
Relative density (g/cm³):	0.85 – 0.99
Water solubility:	Insoluble
pH:	Not Applicable

10. Stability and reactivity

Conditions to avoid:	Sources of ignition
Materials to avoid:	May react with strong oxidising agents.
Hazardous decomposition products:	See 'Fire Fighting Measures'.

11. Toxicological information

Acute oral toxicity:	Harmful: May cause lung damage if swallowed. Aspiration of liquid may cause pulmonary oedema.
Acute inhalation toxicity:	The vapour has anaesthetic properties and when inhaled at concentrations above the Occupational Exposure Limit, it may cause respiratory irritation, headache, fatigue, dizziness and incoordination.
Skin irritation:	May cause skin irritation. Repeated or prolonged contact may cause defatting of the skin resulting in dryness, cracking and dermatitis.
Eye contact:	May cause eye irritation.

12. Ecological information

Environmental Hazards:	Little danger to environment
Mobility:	Floats on water. Large volumes may penetrate soil and could contaminate groundwater.
Degradability:	Oxidises rapidly by photochemical reactions in air
Acute Fish Toxicity:	No acute toxicity to aquatic organisms is expected at maximum water solubility of this material. Long term adverse effects to aquatic organisms are not expected.

13. Disposal considerations

Disposal method: Disposal should be in accordance with local, state or national legislation.

14. Transport information

The product is not subject to transport regulations (ADR/RID, IATA/ICAO and IMDG).

15. Regulatory information

Classification according to EEC directives

Classification: Not classified

Hazard labels: Not classified

Risk phrases: Not classified

Safety phrases: Wear suitable gloves (S37)

16. Other information

This data sheet was prepared in accordance with Directive 91/155/EEC and 1999/45/EC (and relevant amendments).

The information on this sheet is not a specification, it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage and use of the product. It is not applicable to unusual or non-standard uses of the product, nor where instructions or recommendations are not followed.
